


LYRUSFLEX

ELITE SERIES



MESA



REEF



GLACIER



SNOW



GRAND




UINTA



ZION



LASSEN




TETON



NEBO



TIMPANOGAS



DELANO

LYRUSFLEX

ELITE SERIES

Specifications:

Material: 100% virgin vinyl with fiberglass stability layer

Plank Size: 9" x 60" | 18" x 36"

Thickness: 5 mm

Wear Layer: 30 mils ceramic bead infused

Finish: Natural matte emboss

Bevel: Micro-beveled edge

Installation Method: Loose lay/glue down

Plank Visuals (2x unique): Real Grain Technology

Features:

- **Waterproof**
- **Pet Friendly**
- **Stain Resistant**
- **Dent Resistant**

Packaging:

SQ/FT per Carton (9" x 60"): 30.0

SQ/FT per Carton (18" x 36"): 27.0

Warranties:

Multifamily/Residential: 20 Years

Medium Commercial: 10 Years

Certification:


- **SCS Floorscore Certified**
- **Green Guard Gold**

LYRUSFLEX

PREMIUM SERIES



MESA



REEF



GLACIER



SNOW



GRAND




UINTA



ZION



LASSEN




TETON



NEBO



TIMPANOGAS



DELANO

LYRUSFLEX PREMIUM SERIES

Specifications:

Material: Stone Polymer Composite

Plank Size: 9" x 72"

Thickness: 3 mm

Wear Layer: 20 mils ceramic bead infused

Finish: Natural matte embossed

Bevel: Mirco-beveled edge

Installation Method: Glue down

Plank Visuals (2x Unique): Real Grain Technology

Features:

- **Waterproof**
- **Pet Friendly**
- **Stain Resistant**
- **Sound Absorption***

* ASTM E492-09 Impact Sound Conduction IIC 57

Packaging:

SQ/FT per Carton (9" x 60"): 45

SQ/FT per Carton (18" x 36"): 45

Warranties:

Multifamily/Residential: 20 Years


Medium Commercial: 10 Years

Certification:

- **SCS Floorscore Certified**

STONE COMPOSITE

ELITE SERIES



MESA



LASSEN



GRAND



JOSHUA



MAMMOTH



ZION



UINTA



REEF



WRANGELL



KOBUK



KENAI



KATMAI



GATES



BASIN



CUYAHOGA



DENALI



CASCADE



SHENANDOAH



GLACIER



SPRINGS



SNOW



BEND



PINNACLE



TETON



BISCAYNE



ROYALE



SAGUARO



ACADIA



CARLSBAD



CONGAREE

STONE COMPOSITE ELITE SERIES

Specifications:

Material: Stone Polymer Composite

Plank Size: 9" x 72"

Thickness: 5 mm (core) + 1.5 mm (pad)

Wear Layer: 30 mils (ceramic bead infused)

Plank Visuals (2x unique): Real Grain Technology

Finish: Matte finish embossed in register

Bevel: Enhanced beveled edge

Attached Pad: 1.5 mm acoustical IXPE

Installation Method: Unilin Locking System

Features:

- **Waterproof**
- **Pet Friendly**
- **Stain Resistant**
- **Sound Absorption***

* ASTM E492-09 Impact Sound Conduction IIC 57

Packaging:

SQ/FT per Carton: 27

Warranties:

Multifamily/Residential: 20 Years


Medium Commercial: 10 Years

Certification:


- **SCS Floorscore Certified**

STONE COMPOSITE


PREMIUM SERIES




PLACID



PONDEROSA



KODACHROME



EDNESS



GUNLOCK



YUBA



PALISADE




GUERNSEY




BRUNEAU



ACKLEY



KITSAP



BANNACK



DAROGA




VEGA




SYLVAN



FREMONT



LORY



BARR



GLENDO

STONE COMPOSITE PREMIUM SERIES

Specifications:

Material: Stone Polymer Composite

Plank Size: 9" x 60"

Thickness: 4.5 mm (core) + 1.5 mm (pad)

Wear Layer: 20 mils (ceramic bead infused)

Plank Visuals (2x unique): Real Grain Technology

Finish: Matte finish natural embossed

Bevel: Enhanced beveled edge

Attached Pad: 1.5 mm acoustical IXPE

Installation Method: Unilin Locking System

Features:

- **Waterproof**
- **Pet Friendly**
- **Stain Resistant**
- **Sound Absorption***

* ASTM E492-09 Impact Sound Conduction IIC 57

Packaging:

SQ/FT per Carton: 33.60

Warranties:

Multifamily/Residential: 20 Years

Medium Commercial: 10 Years

Certification:


- **SCS Floorscore Certified**
- **Green Guard Gold**

STONE COMPOSITE


SELECT SERIES



ZION



REEF



UINTA



MESA



LASSEN



GRAND



GLACIER



SNOW



TETON

STONE COMPOSITE SELECT SERIES

Specifications:

Material: Stone Polymer Composite

Plank Size: 7" x 60"

Thickness: 4 mm (core) + 1.5 mm (attached IXPE pad)

Wear Layer: 20 mil

Finish: Matte finish embossed in register

Bevel: Micro beveled edge

Attached Pad: 1.5 mm acoustical IXPE

Installation Method: Unilin Locking System

Features:

- **Waterproof**
- **Pet Friendly**
- **Stain Resistant**
- **Sound Absorption***

* ASTM E492-09 Impact Sound Conduction IIC 57

Packaging:

SQ/FT per Carton: 29.70

Warranties:

Multifamily/Residential: 20 Years

Medium Commercial: 10 Years

Certification:

- **SCS Floorscore Certified**
- **Green Guard Gold**

Composition



Transitions

